



- 1.Design According to : DIN3352
- 2.Face to Face Dimension according to EN558-1 14 Series.
- 3.Flange Drilling according to EN1092-2 PN16.
- 4.Test According to ISO 5208.

DN	L	ØD	ØD1	ØD2	b	n-Ød	H	Øz
50	150	Ø165	Ø125	Ø99	19	4-Ø19	423	20
65	170	Ø185	Ø145	Ø118	19	4-Ø19	450	20
80	180	Ø200	Ø160	Ø132	19	8-Ø19	535	26
100	190	Ø220	Ø180	Ø156	19	8-Ø19	590	26
125	200	Ø250	Ø210	Ø184	19	8-Ø19	713	30
150	210	Ø285	Ø240	Ø211	19	8-Ø23	790	30
200	230	Ø340	Ø295	Ø266	20	12-Ø23	974	32
250	250	Ø405	Ø355	Ø319	22	12-Ø28	1185	32
300	270	Ø460	Ø410	Ø370	24.5	12-Ø28	1375	32

20	Disc	DI+EPDM/NBR		
19	Disc nut	Brass		
18	Pin	35		
17	Bolt	Galvanized steel		
16	Packing	EPDM/NBR		
15	Stem	SS420		
14	Washer	Brass		
13	Nut	Galvanized steel		
12	Handwheel	Ductile iron		
11	Stem nut	Brass		
10	Packing gland	Ductile iron		
9	Bolt	Galvanized steel		
8	Nut	Galvanized steel		
7	Washer	Galvanized steel		
6	Yoke	Ductile iron		
5	O-ring	EPDM/NBR		
4	V-ring	EPDM/NBR		
3	Bonnet	Ductile iron		
2	Gasket	EPDM/NBR		
1	Body	Ductile iron		
No	Name	Material	Q'ty	Remark

DRN	wang	WEIGHT		MATERIAL	
CHK		SCALE		Gate Valve	
APP		DATE	07/19/2024		
				CZ0048	
				REV	20240719A