


**Specification**

- 1.Face to Face : EN558-1
- 2.Flange drilling : EN1092-2 PN16.
- 3.Working pressure: PN16
- 4.Pressure band: 20-80Kpa

No	Name	Material
1	Body	GJS450
2	Basket	AISI 304
3	Disc	AISI 304
4	Testing Point	Brass
5	Nut	AISI 304
6	Diaphragm cavity	AISI 304
7	Diaphragm	NBR/EPDM
8	Disc	AISI 304
9	Disc	AISI 304
10	Plug	AISI 304
11	Bonnet	GJS450
12	O-ring	NBR/EPDM
13	Stuffing nut	Brass
14	Dust guard	NBR/EPDM
15	Pin	AISI 304
16	Nut	AISI 304
17	Nut	AISI 304
18	Spindle	AISI 304
19	Spring back	AISI 304
20	Spring	AISI 304
21	Cover	PE
22	Stem	AISI 304
23	Joint	Brass
24	Impulse tube	Copper
25	O-ring	NBR/EPDM

DN	L	ΦD	ΦD1	ΦD2	n-Φd	b	f	A	H(Max)
DN65	290	Φ185	Φ145	Φ118	4-Φ19	19	3	185	420
DN80	310	Φ200	Φ160	Φ132	8-Φ19	19	3	195	435
DN100	350	Φ220	Φ180	Φ156	8-Φ19	19	3	225	460
DN125	400	Φ250	Φ210	Φ184	8-Φ19	19	3	255	480
DN150	480	Φ285	Φ240	Φ211	8-Φ23	19	3	280	505
DN200	600	Φ340	Φ295	Φ266	12-Φ23	20	3	332	745
DN250	730	Φ405	Φ355	Φ319	12-Φ28	22	3	380	840

DRN	wang	WEIGHT		MATERIAL	
CHK		SCALE		Differential pressure valve	
APP		DATE	07/19/2024		
				CM0038	
				REV	240719a

This document is the property of Huihua Valve Industry Co. Distribution of this document without the written consent of the owner is strictly forbidden. Failure to comply will incur a liability for damages.

http://www.hiwa.cn Website sales@hiwa.cn Email

86 - 533 - 6077200 Phone 86 - 533 - 6077233 FAX

Huihua Valve Industry co. No.36 MinAn Road New Hi-Tech Industry Zone Zibo Shandong China 255088 p.c