



Design standard:EN1349/EN1074-5
 Face to Face:EN1349:2000/1074-2000
 Flange Drilling:EN1092-2-PN10/PN16
 Pressure Test:EN12266,API598,ISO5208
 This valve is a pressure reducing valve used to maintain line pressure.

DN	L	D	D1	EN1092-2-PN10		EN1092-2-PN16		b
				D0	nxΦd	D0	nxΦd	
50	230	165	99	125	4X19	125	4X19	19
65	290	185	118	145	4x19	145	4x19	18
80	310	200	132	160	8x19	160	8x19	18
100	350	220	156	180	8x19	180	8x19	18
150	480	285	211	240	8x23	240	8x23	18
200	600	340	266	295	8X23	295	12x23	20
250	730	400	319	350	12X23	355	12x28	22
300	850	460	370	400	12X23	410	12x28	24.5

DN		WEIGHT		MATERIAL	
CHK		SCALE		Pilot pressure reduce valve	
APP		DATE	07/02/2020		
Hiwa				CM0002	
				REV	20200702A

This document is the property of Huhua Valve Industry Co.
 Distribution of this document without the written consent of the owner is strictly forbidden.
 Failure to comply will incur a liability for damages.

<http://www.hiwa.cn> Website
 sales@hiwa.cn Email

FAX
 86-533-8077200 Phone
 86-533-8077233

Hiwa Valve Industry Co.
 No.36 Minxin Road New Hi-Tech Industry
 Zone Zibo Shandong China 255008 p.c