


Design standard: EN1349/EN1074-5
 Face to Face: EN1349:2000/1074-2000
 Flange Drilling: EN1092-2-PN10/PN16
 Pressure Test: EN12266, API598, ISO5208
 This valve is a pressure reducing valve used to maintain
 line pressure.

DN	L	D	D1	EN1092-2-PN10		EN1092-2-PN16		b
				D0	n \times ϕ d	D0	n \times ϕ d	
50	230	165	99	125	4 \times 19	125	4 \times 19	19
65	290	185	118	145	4 \times 19	145	4 \times 19	18
80	310	200	132	160	8 \times 19	160	8 \times 19	18
100	350	220	156	180	8 \times 19	180	8 \times 19	18
150	480	285	211	240	8 \times 23	240	8 \times 23	18
200	600	340	266	295	8 \times 23	295	12 \times 23	20
250	730	400	319	350	12 \times 23	355	12 \times 28	22
300	850	460	370	400	12 \times 23	410	12 \times 28	24.5

DRN	WEIGHT	MATERIAL	
CRK	SCALE		
APP	DATE	07/02/2020	
Pilot pressure Sustaining Valve			



CM0003

REV 20200202

This document is the property of Hiwa Valve Industry Co.
 Distribution of this document without the written consent of the owner is strictly forbidden
 Failure to comply will incur a liability for damages

<http://www.hiwa.cn> Website
 sales@hiwa.cn Email

86-533-8077200 Phone
 86-533-8077233 FAX

Hiwa Valve Industry Co.
 No.36 Min'an Road New Hi-Tech Industry
 Zone Zibo Shandong China 255008 p.c.