



Nominal pressure		PN16
Test pressure	Strength test	2.4Mpa
	Sealing test	1.76Mpa
Maximum working temperature		-10°C to +90°C
Suitable Media		W.O.G etc

- 1.Design and manufacture according to API 609.
- 2.Face to face according to DIN3202-K1.
- 3.Flange drilling according to EN1092-2 PN16.
- 4.Top flange drilling according to ISO 5211.
- 5.Pressure test according to API598.

DN	L	H1±5(Max)	H2±5(Max)	H3	ΦC	n-M	Top Flange	ΦN	ΦC1	n1-Φd1	HxH
350	78	330	263	45	470	16-M24	F10	125	102	4-12	22x22
400	102	361	293	51.2	525	16-M27	F14	175	140	4-18	22x22
450	114	400	324	51.2	585	20-M27	F14	175	140	4-18	27x27
500	127	465	351	64.2	650	20-M30	F14	175	140	4-18	27x27
600	154	568	446	70.2	770	20-M33	F16	210	165	4-22	36x36

Item	Part name	Material	Q'ty	Remark
6	Seal Ring	EPDM		
5	Bushing	PTFE		
4	Seat	EPDM		
3	Stem	Stainless Steel		
2	Disc	Ductile Iron		
1	Body	Ductile Iron		

DRN	wang	WEIGHT		MATERIAL
CHK		SCALE		Butterfly Valve
APP		DATE	07/25/2024	
				B20L-HJ
				REV

This document is the property of Huihua Valve Industry Co. Distribution of this document without the written consent of the owner is strictly forbidden. Failure to comply will incur a liability for damages.

Huihua Valve Industry co. No.36 MinAn Road New Hi-Tech Industry Zone Zibo Shandong China 255088 p.c

http://www.hiwa.cn Website sales@hiwa.cn Email

86 - 533 - 6077200 Phone 86 - 533 - 6077233 FAX